

SSL0612-24V12W

WATTAGE	LUMEN	BEAM	CRI	CCT	SDCM	INPUT	DIM	CERTIFICATE	LEDs	IP	Warranty
12W/M	650lm/m 680lm/m 720lm/m 760lm/m	120°	>90 R9>50	2500k 2700k 3000k Customized	3 step	DC12V/ DC24V	Dali/ 0-10V/ Triac	CE RoHS	120pcs 50mm LED pitch	67	2 years

■ Product Photo











■Structural Drawing



■Light Distribution Curve



Notes: • Can't work in same circuit with inductive ballast.

- Not suitable for enclosed lighting fixtures.
- Dimming compatibility list is available for reference.

SEGULA

SSL1010-12V12W-2700K

WATTAGE	LUMEN	BEAM	CRI	CCT	SDCM	INPUT	DIM	CERTIFICATE	LEDs	IP	Warranty
12W/M	860lm/m	120°	>90	2500k	3 step	DC12V/	Dali/	CE RoHS	120pcs	67	2 years
	880lm/m		R9>50	2700k		DC24V	0-10V/		8.33mm		
	900lm/m			3000k			Triac		LED pitch		
	920lm/m			Customized							

■ Product Photo













Structural Drawing

Foursquare surface



Light Distribution Curve



SSL1219-24V15W-2700K

WATTAGE	LUMEN	BEAM	CRI	CCT	SDCM	INPUT	DIM	CERTIFICATE	LEDs	IP	Warranty
14.4W/M	680lm/m	120°	>90	2500k	3 step	DC12V/	Dali/	CE RoHS	120pcs	67	2 years
	700lm/m		R9>50	2700k		DC24V	0-10V/		50mm		
	750lm/m			3000k			Triac		LED pitch		
	800lm/m			Customized							

■ Product Photo













■Structural Drawing



■Light Distribution Curve



SEGULA

SSL0812-24V12W-2700K


WATTAGE	LUMEN	BEAM	CRI	ССТ	SDCM	INPUT	DIM	CERTIFICATE	LEDs	IP	Warranty
12W/M	400lm/m	120°	>90	2500k	3 step	DC12V/	Dali/	CE RoHS	120pcs	67	2 years
	420lm/m		R9>50	2700k		DC24V	0-10V/		8.33mm		
	430lm/m			3000k			Triac		LED pitch		
	450lm/m			Customized							

■ Product Photo






Structural Drawing





Side Emitting

Light Distribution Curve



SSL-161612W-2700K


WATTAGE	LUMEN	BEAM	CRI	CCT	SDCM	INPUT	DIM	CERTIFICATE	LEDs	IP	Warranty
14.4W/M	1040lm/m 1080lm/m 1150lm/m	120°	>90 R9>50	2500k 2700k 3000k Customized	3 step	DC12V/ DC24V	Dali/ 0-10V/ Triac	CE RoHS	120pcs 7.14mm LED pitch	67	2 years

■ Product Photo






■Structural Drawing





Foursquare surface

■Light Distribution Curve





SEGULA

SSL0812-24V12W-2700K Ambient

WATTAGE	LUMEN	BEAM	CRI	CCT	SDCM	INPUT	DIM	CERTIFICATE	LEDs	IP	Warranty
14.4W/M	180lm/m ~ 220lm/m	120°	>90 R9>50	2500k ~ 6000k	3 step	DC12V/ DC24V	Dali/ 0-10V/ Triac	CE RoHS	196pcs 71.4mm LED pitch	67	2 years


■ Product Photo








■Structural Drawing






Light Distribution Curve









The new Segula Vivid Line is a major breakthrough in LED Technology with the color spectrum incorporate with over 1 billion colors within its wavelength. The Vivid Line provides the optional lighting balance for the space and enhance the appearance of interiors — making wood, food and skin tones appear more natural and lifelike. Segula believes light is not just a media that provides brightness, light is the essence of visual storytelling and refined emotion.

SEGULA VIVID LED




REGULAR LED



Bending


Incorrect




Cutting profile should be flat



No twisting



No bending up and down the light surface




No 90° bending




No bending repeatedly


Packaging



12 inch *12 mm Standard Length: 5 meters /roll



305*305*38 mm 2 rolls per box



405*320*328

10 boxes per carton
Gross weight: 18 kgs



- 1, to fix the clips onto the mounting surface, 3 pcs per meter recommended;
- 2, to fix the silicon light strip into the clips

Optional Accessories

Name	Aluminum clip	Aluminum profile	Silicone glue	Steel Profile	Caps
Illustration					
Remarks	L: 20 mm	L: 1000 mm	10 ml /pc		

Contact

Segula International Limited

- 852 3954 5598
- https://www.segula.design
- in@segula.de, mh@segula.lighting
- 7/A, 9/F, Block B, Hong Kong Industrial Center, Lai Chi Kok, Kowloon, Hong Kong